

Manager API

Введение

Для работы с интерфейсом событий существует несколько вариантов взаимодействия.

/arawman => Raw HTTP Manager Event Interface with Digest authentication

/rawman => Raw HTTP Manager Event Interface

/amxml => XML Manager Event Interface with Digest authentication

/mxml => XML Manager Event Interface

Документация описывает взаимодействие с интерфейсом событий через необработанные HTTP запросы. Аналогичная документация применима и к другим вариантам.

Авторизация

GET /rawman?action=login

Параметр	Тип	Обязательный	Описание
username	String	Да	Пользователь
secret	String	Да	Пароль

Пример запроса: <http://<ip>:8088/rawman?action=login&username=test&secret=test>

Пример ответа:

Response: Success

Message: Authentication accepted

Проверка доступности

GET /rawman?action=ping

Пример ответа:

Response: Success

Ping: Pong

Timestamp: 1711272193.709205

Запрос статуса телефонной станции

GET /rawman?rawman?action=status

Параметр	Тип	Обязательный	Описание
actionid	String	Нет	Идентификатор запроса
channel	String	Нет	Канал
variables	String	Нет	Переменные
allvariables	Boolean	Нет	Все переменные

Пример ответа:

```
Response: Success
EventList: start
Message: Channel status will follow

Event: Status
Privilege: Call
Channel: PJSIP/user
ChannelState: 6
ChannelStateDesc: Up
CallerIDNum: 110
CallerIDName:
ConnectedLineNum: <unknown>
ConnectedLineName: <unknown>
Language: ru
AccountCode:
Context: outgoing
Exten: 153
Priority: 3
Uniqueid: 1711273253.11
Linkedid: 1711273253.11
Type: PJSIP
DNID: 153
EffectiveConnectedLineNum: <unknown>
EffectiveConnectedLineName: <unknown>
```

TimeToHangup: 0
BridgeID:
Application: Queue
Data: queue
Nativeformats: (alaw)
Readformat: alaw
Readtrans:
Writeformat: slin
Writetrans: (slin@8000)->(alaw@8000)
Callgroup: 0
Pickupgroup: 0
Seconds: 21

Event: StatusComplete
EventList: Complete
ListItems: 1
Items: 1

Запрос создания звонка

GET /rawman?rawman?action=originate

Параметр	Тип	Обязательный	Описание
actionid	String	Нет	Идентификатор запроса
channel	String	Да	Канал
exten	String	Да	Расширение
context	String	Да	Маршрутизация
priority	Integer	Да	Приоритет
application	String	Нет	Приложение
data	String	Да	Данные приложение
timeout	Integer	Да	Таймаут
callerid	String	Нет	АОН
variable	String	Нет	Переменные
account			

Параметр	Тип	Обязательный	Описание
earlymedia			
async	Boolean	Нет	Асинхронный ввод
codecs			
channelid			
otherchannelid			

Пример запроса:

<http://<ip>:8088/rawman?action=originate&channel=PJSIP/user&context=outgoing&exten=100&priority=1&async=true>

Список команд

GET /rawman?action=listcommands

Пример ответа:

Response: Success

AbsoluteTimeout: Set absolute timeout. (Priv: system,call,all)

AGI: Add an AGI command to execute by Async AGI. (Priv: agi,all)

AOCMessage: Generate an Advice of Charge message on a channel. (Priv: aoc,all)

Atxfer: Attended transfer. (Priv: call,all)

BlindTransfer: Blind transfer channel(s) to the given destination (Priv: call,all)

Bridge: Bridge two channels already in the PBX. (Priv: call,all)

BridgeDestroy: Destroy a bridge. (Priv: <none>)

BridgeInfo: Get information about a bridge. (Priv: <none>)

BridgeKick: Kick a channel from a bridge. (Priv: <none>)

BridgeList: Get a list of bridges in the system. (Priv: <none>)

BridgeTechnologyList: List available bridging technologies and their statuses. (Priv: <none>)

BridgeTechnologySuspend: Suspend a bridging technology. (Priv: <none>)

BridgeTechnologyUnsuspend: Unsuspend a bridging technology. (Priv: <none>)

CancelAtxfer: Cancel an attended transfer. (Priv: call,all)

Challenge: Generate Challenge for MD5 Auth. (Priv: <none>)

Command: Execute Asterisk CLI Command. (Priv: command,all)

ConfbridgeKick: Kick a Confbridge user. (Priv: call,all)

ConfbridgeList: List participants in a conference. (Priv: reporting,all)

ConfbridgeListRooms: List active conferences. (Priv: reporting,all)

ConfbridgeLock: Lock a Confbridge conference. (Priv: call,all)

ConfbridgeMute: Mute a Confbridge user. (Priv: call,all)

ConfbridgeSetSingleVideoSrc: Set a conference user as the single video source distributed to all other participants. (Priv: call,all)

ConfbridgeStartRecord: Start recording a Confbridge conference. (Priv: system,all)

ConfbridgeStopRecord: Stop recording a Confbridge conference. (Priv: system,all)

ConfbridgeUnlock: Unlock a Confbridge conference. (Priv: call,all)

ConfbridgeUnmute: Unmute a Confbridge user. (Priv: call,all)

CoreSettings: Show PBX core settings (version etc). (Priv: system,reporting,all)

CoreShowChannelMap: List all channels connected to the specified channel. (Priv: system,reporting,all)

CoreShowChannels: List currently active channels. (Priv: system,reporting,all)

CoreStatus: Show PBX core status variables. (Priv: system,reporting,all)

CreateConfig: Creates an empty file in the configuration directory. (Priv: config,all)

DBDel: Delete DB entry. (Priv: system,all)

DBDelTree: Delete DB Tree. (Priv: system,all)

DBGet: Get DB Entry. (Priv: system,reporting,all)

DBGetTree: Get DB entries, optionally at a particular family/key (Priv: system,reporting,all)

DBPut: Put DB entry. (Priv: system,all)

DialplanExtensionAdd: Add an extension to the dialplan (Priv: system,all)

DialplanExtensionRemove: Remove an extension from the dialplan (Priv: system,all)

Events: Control Event Flow. (Priv: <none>)

ExtensionState: Check Extension Status. (Priv: call,reporting,all)

ExtensionStateList: List the current known extension states. (Priv: call,reporting,all)

FAXSession: Responds with a detailed description of a single FAX session (Priv: call,all)

FAXSessions: Lists active FAX sessions (Priv: call,all)

FAXStats: Responds with fax statistics (Priv: reporting,all)

Filter: Dynamically add filters for the current manager session. (Priv: system,all)

GetConfig: Retrieve configuration. (Priv: system,config,all)

GetConfigJSON: Retrieve configuration (JSON format). (Priv: system,config,all)

Getvar: Gets a channel variable or function value. (Priv: call,reporting,all)

Hangup: Hangup channel. (Priv: system,call,all)

ListCategories: List categories in configuration file. (Priv: config,all)

ListCommands: List available manager commands. (Priv: <none>)

LocalOptimizeAway: Optimize away a local channel when possible. (Priv: system,call,all)

LoggerRotate: Reload and rotate the Asterisk logger. (Priv: system,reporting,all)

Login: Login Manager. (Priv: <none>)

Logoff: Logoff Manager. (Priv: <none>)

MailboxCount: Check Mailbox Message Count. (Priv: call,reporting,all)

MailboxStatus: Check mailbox. (Priv: call,reporting,all)

MessageSend: Send an out of call message to an endpoint. (Priv: message,all)

MixMonitor: Record a call and mix the audio during the recording.
Use of StopMixMonitor is required to guarantee the audio file

is available for processing during dialplan execution. (Priv: system,all)

MixMonitorMute: Mute / unMute a Mixmonitor recording. (Priv: system,call,all)

ModuleCheck: Check if module is loaded. (Priv: system,all)

ModuleLoad: Module management. (Priv: system,all)

Originate: Originate a call. (Priv: originate,all)

Ping: Keepalive command. (Priv: <none>)

PJSIPHangup: Hangup an incoming PJSIP channel with a SIP response code (Priv: system,call,all)

PJSIPQualify: Qualify a chan_pjsip endpoint. (Priv: system,reporting,all)

PJSIPRegister: Register an outbound registration. (Priv: system,reporting,all)

PJSIPShowAors: Lists PJSIP AORs. (Priv: system,all)

PJSIPShowAuths: Lists PJSIP Auths. (Priv: system,all)

PJSIPShowContacts: Lists PJSIP Contacts. (Priv: system,all)

PJSIPShowEndpoint: Detail listing of an endpoint and its objects. (Priv: system,all)

PJSIPShowEndpoints: Lists PJSIP endpoints. (Priv: system,all)

PJSIPShowRegistrationInboundContactStatuses: Lists ContactStatuses
for PJSIP inbound registrations. (Priv: system,all)

PJSIPShowRegistrationsInbound: Lists PJSIP inbound registrations. (Priv: system,all)

PJSIPShowRegistrationsOutbound: Lists PJSIP outbound registrations. (Priv: system,reporting,all)

PJSIPShowResourceLists: Displays settings for configured resource lists. (Priv: system,all)

PJSIPShowSubscriptionsInbound: Lists subscriptions. (Priv: system,all)

PJSIPShowSubscriptionsOutbound: Lists subscriptions. (Priv: system,all)

PJSIPUnregister: Unregister an outbound registration. (Priv: system,reporting,all)

PresenceState: Check Presence State (Priv: call,reporting,all)

QueueAdd: Add interface to queue. (Priv: agent,all)

QueueChangePriorityCaller: Change priority of a caller on queue. (Priv: <none>)

QueueLog: Adds custom entry in queue_log. (Priv: agent,all)

QueueMemberRingInUse: Set the ringinuse value for a queue member. (Priv: agent,all)

QueuePause: Makes a queue member temporarily unavailable. (Priv: agent,all)

QueuePenalty: Set the penalty for a queue member. (Priv: agent,all)

QueueReload: Reload a queue, queues, or any sub-section of a queue or queues. (Priv: <none>)

QueueRemove: Remove interface from queue. (Priv: agent,all)

QueueReset: Reset queue statistics. (Priv: <none>)

QueueRule: Queue Rules. (Priv: <none>)

QueueStatus: Show queue status. (Priv: <none>)

QueueSummary: Show queue summary. (Priv: <none>)

QueueWithdrawCaller: Request to withdraw a caller from the queue back to the dialplan. (Priv: <none>)

Redirect: Redirect (transfer) a call. (Priv: call,all)

Reload: Send a reload event. (Priv: system,config,all)

SendText: Sends a text message to channel. A content type
can be optionally specified. If not set it is set to an empty

string allowing a custom handler to default it as it sees fit. (Priv: call,all)

Setvar: Sets a channel variable or function value. (Priv: call,all)

ShowDialPlan: Show dialplan contexts and extensions (Priv: config,reporting,all)

Status: List channel status. (Priv: system,call,reporting,all)

StopMixMonitor: Stop recording a call through MixMonitor,
and free the recording's file handle. (Priv: system,call,all)

UpdateConfig: Update basic configuration. (Priv: config,all)

UserEvent: Send an arbitrary event. (Priv: user,all)

WaitEvent: Wait for an event to occur. (Priv: <none>)

Описание команд

GET /rawman?action=command&command=manager show command waitevent

Пример ответа:

Response: Success
Message: Command output follows
Output: [Syntax]
Output: Action: WaitEvent
Output: [ActionID:] <value>
Output: Timeout: <value>
Output:
Output: [Synopsis]
Output: Wait for an event to occur.
Output:
Output: [Description]
Output: This action will elicit a 'Success' response. Whenever a manager event is
Output: queued. Once WaitEvent has been called on an HTTP manager session, events will
Output: be generated and queued.
Output:
Output: [Arguments]
Output: ActionID
Output: ActionID for this transaction. Will be returned.
Output: Timeout
Output: Maximum time (in seconds) to wait for events, '-1' means forever.
Output:
Output: [See Also]
Output: Not available
Output:
Output: [Privilege]
Output: <none>
Output:
Output: [List Responses]
Output: None
Output:
Output: [Final Response]
Output: None
Output:
Output:

Revision #13

Created 24 March 2024 09:02:48 by Тимофей Пупышев

Updated 25 March 2024 20:56:36 by Тимофей Пупышев